1946-48 FORD MAINTENANCE RECORD

Date _____ Mileage _____

1000 Miles

Lubricate the following:

- ☐ Door Hinges, Latches and Stops
- ☐ Dovetails and Striker Plates
- ☐ Accelerator Linkages
- ☐ Hood and Trunk Latch
- ☐ Generator
- ☐ Gear Shift Levers
- ☐ Spindles
- ☐ Tie Rod Ends
- ☐ Drag Link
- ☐ Clutch Equalizer Shaft
- ☐ Clutch and Brake Pedals
- ☐ U-Joint
- ☐ Drive Shaft
- ☐ Rear Spring Center

Add oil to:

- ☐ Differential
- ☐ Transmission
- ☐ Steering Gear

Check the following:

- ☐ Tire Pressures 28 p.s.i.
- ☐ Play in front king pins and steering linkages
- ☐ Battery Water level
- ☐ Radiator Water level

And:

- ☐ Clean Breather Cap
- ☐ Adjust brakes

5000 Miles

Lubricate the following:

- ☐ Fan
- ☐ Clutch Release Shaft
- ☐ Rear Spring Cover
- ☐ Speedometer

And:

- ☐ Change Transmission Oil
- ☐ Rotate Tires
- ☐ Check Spark Plugs to clean
- ☐ Change oil and filter and in air cleaner S.A.E. 30
- ☐ Clean Settling Bowl
- ☐ Add brake fluid to master cylinder

10,000 miles

- ☐ Re-pack Wheel Bearings
- ☐ Replace Brake Shoes
- ☐ Replace Points, Condenser, Rotor and Spark Plugs
- ☐ Check Clutch Pedal play and adjust
- ☐ Replace Windshield Wipers
- ☐ Align Front Wheels

Spring

- ☐ Remove Differential Oil and replace with S.A.E. 140 oil for summer

Fall

- ☐ Remove differential oil and replace with S.A.E. 90 oil for winter
- ☐ Check anti-freeze