Form 3027 50M — 5-27-30

# NEW TRUCK DIRECTIONS

**SPEED** Avoid high speeds while truck is new. To obtain best results, IT SHOULD NOT BE DRIVEN FASTER THAN 20 MILES PER HOUR FOR THE FIRST 500 MILES.

**OIL** Keep the oil at "F" on the measuring rod, especially during the first few hundred miles. Never let it get below the mark "L". Remove measuring rod and wipe with a dry cloth before testing the level. OIL SHOULD BE CHANGED AFTER THE FIRST 500 MILES AND EVERY 500 MILES THEREAFTER. Summer oil should conform to S. A. E. specification 40, and Winter oil to S. A. E. specification 20. The oil in the rear axle must be kept up to the level of the filler plug opening at all times.

**BRAKES** This truck is equipped with 4-wheel mechanical brakes which are quick and positive in action. Keep the truck under control at all times to avoid the necessity for sudden application of brakes which might result in collision from rear.

**FAN BELT** Do not tighten fan belt. The V-type fan belt does not require tight adjustment for proper operation. Too tight an adjustment will result in excessive wear on fan belt and generator bearings, particularly at higher speeds.

**TIRES** For proper braking and long life keep tires inflated as follows: 45 pounds for 6.00 x 20 tires and 30 pounds for 32 x 6 tires.

**INSPECTION** To insure best results have an Authorized FORD DEALER (preferably the Dealer from whom you purchased your truck) inspect this truck and make necessary minor adjustments after the first five hundred miles of running.

**TRIPLEX SAFETY GLASS** For your protection, Triplex Safety Glass is used in the windshield of this truck. Do not replace Triplex Safety Glass with plate glass. When replacement is necessary use TRIPLEX SAFETY GLASS.

## DRIVE SAFELY

**FORD MOTOR COMPANY**

B. Terry Vintage Automotive
www.Model-A-Ford.com