SPEEDOMETER GEAR CHART

§ 1928-48 PASSENGER AND 1928-41 COMMERCIAL WITH THREE SPEED TRANSMISSION

USED WITH 9-34 REAR AXLE (3.78 TO 1 RATIO)		USED WITH 9-37 REAR AXLE (4.111 TO 1 RATIO)		USED WITH 9-39 REAR AXLE (4.333 TO 1 RATIO)		USED WITH 9-40 REAR AXLE (4.44 TO 1 RATIO)		USED WITH 9-41 REAR AXLE (4.55 TO 1 RATIO)		USED WITH 11-39 REAR AXLE (3.54 TO 1 RATIO)		USED WITH 11-40 REAR AXLE (3.63 TO 1 RATIO)		USED WITH TIRE	
•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	•PART NUMBER OF DRIVEN GEAR	NO. TEETH	SIZE	PLY
A 17270-D	19	A 17270-E	21											4.50 x 21	4
A 17270-D	19	A 17270-E	21											4.50 x 21	6
B 17270-A	19	B 17270-B	21											4.75 x 19	4
B 17270-A	19	B 17270-B	21											4.75 x 19	6
B 17270-A	19	B 17270-B	21			18 17270	22	BF 17270	23	40 17270	18			5.25 x 18	4
B 17270-A	19	68 17270-A	20			18 17270	22	18 17270	22	40 17270	18			5.25 x 18	6
B 17270-A	19					18 17270	22	BF 17270	23	40 17270	18			5.50 x 17	4
B 17270-A	19					18 17270	22	BF 17270	23	40 17270	18			5.50 x 17	6
68 17270-A	20	18 17270	22	BF 17270	23	74 17270	24	74 17270	24	B 17270-A	19			5.50 x 16	4
68 17270-A	20	18 17270	22	BF 17270	23	BF 17270	23	74 17270	24	B 17270-A	19			5.50 x 16	6
B 17270-A	19	B 17270-B	21	18 17270	22	BF 17270	23	BF 17270	23	40 17270	18	B 17270-B	21	6.00 x 16	4
B 17270-A	19	B 17270-B	21	18 17270	22	BF 17270	23	BF 17270	23	40 17270	18			6.00 x 16	6
40 17270	18	68 17270-A	20	B 17270-B	21	B 17270-B	21	18 17270	22	68 17270-B	20			6.00 x 18	4
40 17270	18	68 17270-A	20	B 17270-B	21	B 17270-B	21	18 17270	22	68 17270-B	20			6.00 x 18	6
68 17270-A	20	18 17270	22					74 17270	24					6.50 x 15	4
B 17270-A	19	B 17270-B	21	18 17270	22	18 17270	22	BF 17270	23	68 17270-A	20	40 17270	18	6.50 x 16	4
B 17270-A	19	B 17270-B	21	18 17270	22	18 17270	22	BF 17270	23	68 17270-A	20			6.50 x 16	6
40 17270	18	68 17270-A	20			18 17270	22			68 17270-B	20			7.00 x 16	4
40 17270	18	68 17270-A	20			B 17270-B	21			68 17270-B	20			7.00 x 16	6
B 17270-A	19	68 17270-A	20	B 17270-B	21	18 17270	22	BF 17270	23	40 17270	18			7.50 x 15	4
B 17270-A	19	68 17270-A	20	B 17270-B	21	18 17270	22	18 17270	22	68 17270-B	20			7.50 x 15	6
40 17270	18	68 17270-A	20	B 17270-B	21	B 17270-B	21	18 17270	22	68 17270-B	20			9.00 x 13	

• The B 17285 Driving Gear (7 teeth) is used exclusively.

§ Refer to page 630 for model application.